## NSN 5930-01-127-8159

Liquid Level Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-127-8159

| Power Cable Length:   |
|---|
| 24.000 inches   |
| Ac Voltage Rating:  |
| 50.0 volts  |
| Dc Voltage Rating:  |
| 50.0 volts  |
| Frequency Rating:   |
| 60.0 hertz  |
| Overall Diameter:   |
| 2.000 inches  |
| Actuation Method:   |
| Buoyancy  |
| Electrical Connection Type:                                 |
| Cable   |
| Internal Battery Accommodation:                             |
| Not included  |
| Current Rating At Maximum Rated Voltage:                    |
| 0.06 amperes resistive load and 0.04 amperes resistive load |
| Voltage Rating At Maximum Rated Current:                    |
| 50.0 volts  |
| Float Quantity:   |
| 1   |
| Operating Tempurature Rating:                               |
| Between 0.0 degrees fahrenheit and 300.0 degrees fahrenheit |
| Mounting Method:  |
| Thread  |
| Mounting Position:  |
| Vertical  |
| Maximum Current Rating:                                     |
| 0.3 amperes resistive load                                  |
| Contact Arrangement:  |
| Spst, normally closed                                       |
| Relay:  |
| Not included  |
| Float Effective Travel:                                     |
| Any acceptable  |
| Mounting Dimensions:  |
| Mtd by one 2.000 in. Diameter npt plug                      |
| Tank Insertion Length:                                      |
| 17.000 inches   |
| Phase:  |

Single

## NSN 5930-01-127-8159

Liquid Level Switch - Page 2 of 2



|  |  | fe |  |
|--|--|----|--|
|  |  |    |  |

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

T109-d