## NSN 5930-01-127-8638

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-127-8638 **Body Style:** Hole mounted **Center To Center Distance Between Mounting Facilities Parallel To Length:** 0.188 inches **Body Length:** 0.616 inches **Body Width:** 0.316 inches **Body Height:** 0.600 inches **Unthreaded Mounting Hole Diameter:** 0.091 inches **Actuator Style:** Round **Actuator Diameter:** 0.060 inches **Actuator Height:** 0.095 inches **Actuator Free Position Height:** 0.425 inches **Maximum Voltage Rating In Volts:** 28.0 dc **Inclosure Type:** Fully enclosed **Features Provided:** Actuator seal **Nonpile-up Contact Arrangement:** 1 pole, double throw, one position momentary single switch unit **Switch Release Force:** 3.0 ounces **Switch Actuating Force:** Between 5.0 ounces and 17.0 ounces **Actuator Movement:** Between 0.050 pretravel inches and 0.004 overtravel inches and 0.005 differential inches **Contact Load Current Rating At Maximum Rated Voltage:** 1.000 amperes resistive dc and 0.500 amperes inductive dc **Terminal Type And Quantity:** 3 wire lead Shelf Life: N/a

**Unit Of Measure:** 

## NSN 5930-01-127-8638

Sensitive Switch - Page 2 of 2



Demilitarization:

No

Fiig:

A053a0