

View Online at <https://aerobasegroup.com/nsn/5930-01-127-8640>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Fungus proof and waterproof

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.375 inches

Body Length:

0.780 inches

Body Width:

0.250 inches

Body Height:

0.360 inches

Unthreaded Mounting Hole Diameter:

0.088 inches

Actuator Style:

Round

Actuator Diameter:

0.045 inches

Actuator Height:

0.045 inches

Actuator Free Position Height:

0.355 inches

Maximum Voltage Rating In Volts:

250.0 ac and 30.0 dc

Inclosure Type:

Fully enclosed

Features Provided:

Actuator seal

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

40.0 grams

Switch Actuating Force:

150.0 grams

Actuator Movement:

Between 0.020 pretravel inches and 0.007 overtravel inches and 0.003 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

2.500 amperes inductive dc and 4.000 amperes resistive dc and 5.000 amperes resistive ac

Precious Material And Location:

Contacts gold

Terminal Type And Quantity:

3 bus bar

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0