

View Online at <https://aerobasegroup.com/nsn/5930-01-127-8640>

**Body Style:**

Hole mounted

**Hazardous Locations/environmental Protection:**

Fungus proof and waterproof

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

0.375 inches

**Body Length:**

0.780 inches

**Body Width:**

0.250 inches

**Body Height:**

0.360 inches

**Unthreaded Mounting Hole Diameter:**

0.088 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.045 inches

**Actuator Height:**

0.045 inches

**Actuator Free Position Height:**

0.355 inches

**Maximum Voltage Rating In Volts:**

250.0 ac and 30.0 dc

**Inclosure Type:**

Fully enclosed

**Features Provided:**

Actuator seal

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

40.0 grams

**Switch Actuating Force:**

150.0 grams

**Actuator Movement:**

Between 0.020 pretravel inches and 0.007 overtravel inches and 0.003 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

2.500 amperes inductive dc and 4.000 amperes resistive dc and 5.000 amperes resistive ac

**Precious Material And Location:**

Contacts gold

**Terminal Type And Quantity:**

3 bus bar

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0