

View Online at <https://aerobasegroup.com/nsn/5930-01-128-3724>

Thread Class:

2b single pressure connection

Inside Diameter:

0.217 inches single connection

Overall Length:

3.500 inches

Body Length:

2.100 inches

Overall Diameter:

1.762 inches

Unthreaded Mounting Hole Diameter:

0.272 inches

Distance Between Mounting Facility Centers:

1.012 inches

End Application:

Hydraulic sys

Pressure Switch Type:

Gage

Mounting Method:

Unthreaded hole

Thready Qty Per Inch (tpi):

11 single pressure connection

Contact Action Stimulus:

Increase

Proof Pressure:

4500.00 pounds per square inch gage

Thread Size:

0.217 inches single pressure connection

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained

Sensing Element Burst Pressure:

7500.00 pounds per square inch gage

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

50.0 milliamperes resistive load single voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

1800.00 actuation point pounds per square inch gage and 1500.00 deactuation point pounds per square inch gage and 300.00 differential point pounds per square inch gage

Contact Voltage Rating In Volts:

28.0 dc at sea level single voltage

Pressure Connector Type:

Plain, threaded internal single connection

Media For Which Designed:

Gas or liquid

Style Designator:

Cylindrical

Thread Series Designator:

Uns single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A048b0