## NSN 5930-01-128-3739

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-128-3739
Body Style:
Hole mounted
Overall Length:
0.780 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.380 inches
Overall Height:
0.422 inches
Overall Width:
0.250 inches
Body Length:
0.780 inches
Body Width:
0.250 inches
Case Material:
Plastic
Unthreaded Mounting Hole Diameter:
0.087 inches
Actuator Style:
Round
Actuator Diameter:

Actuator Dian

0.090 inches

Actuator Free Position Height:

0.410 inches

Maximum Voltage Rating In Volts:

250.0 ac and 28.0 dc

**End Application:** 

Ship control

Inclosure Type:

Fully enclosed

**Nonpile-up Contact Arrangement:** 

1 pole, double throw, one position momentary single switch unit

**Switch Release Force:** 

28.0 grams

**Switch Actuating Force:** 

Between 57.0 grams and 142.0 grams

**Actuator Movement:** 

Between 0.030 pretravel inches and 0.010 overtravel inches and 0.006 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:** 

5.000 amperes resistive dc and 3.000 amperes inductive dc and 5.000 amperes resistive ac

**Precious Material And Location:** 

Contacts silver

## NSN 5930-01-128-3739

Sensitive Switch - Page 2 of 2



Terminal Type And Quantity:
3 turret
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

**Fiig:** A053a0