

View Online at <https://aerobasegroup.com/nsn/5930-01-128-6283>

Inside Diameter:

0.500 inches single connection

Hazardous Locations/environmental Protection:

Weather resistant and salt spray resistant and fungus proof

Overall Length:

4.375 inches

Overall Height:

7.062 inches

Overall Width:

2.500 inches

Body Height:

5.250 inches

Unthreaded Mounting Hole Diameter:

0.344 inches

Longest Horizontal Distance Between Mounting Centers:

1.974 inches

Longest Vertical Distance Between Mounting Centers:

5.875 inches

Pressure Switch Type:

Gage

Mounting Method:

Bracket and unthreaded hole

Features Provided:

Electrical access port and internally grounded

Contact Action Stimulus:

Increase

Proof Pressure:

4800.00 pounds per square inch gage

Mounting Facility Pattern:

Two position diagonal

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained

Terminal Type:

Screw

Contact Load Current Rating:

10.0 amperes resistive load first voltage

Contact Adjustability:

Actuation point adjustable and deactuation point adjustable

Contact Adjustment Range:

+239.00/+3200.00 actuation point pounds per square inch gage and +160.00/+3121.00 deactuation point pounds per square inch gage

Contact Adjustment Type:

External actuation point screw and external deactuation point screw

Contact Voltage Rating In Volts:

480.0 ac at sea level second voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular w/bracket

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiiig:

A048b0