

View Online at <https://aerobasegroup.com/nsn/5930-01-129-1187>

**Thread Class:**

2a

**Body Style:**

Bushing/hole mounted

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.000 inches

**Bushing Length:**

0.530 inches

**Body Length:**

1.940 inches

**Body Width:**

0.687 inches

**Body Height:**

0.930 inches

**Unthreaded Mounting Hole Diameter:**

0.140 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.320 inches

**Actuator Height:**

1.099 inches

**Actuator Free Position Height:**

1.719 inches

**Maximum Voltage Rating In Volts:**

480.0 ac and 250.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing and unthreaded hole

**Thread Size:**

0.500 inches

**Nonpile-up Contact Arrangement:**

1 pole, single throw, normally open, momentary action single switch unit

**Switch Release Force:**

10.0 ounces

**Switch Actuating Force:**

Between 14.0 ounces and 22.0 ounces

**Actuator Movement:**

Between 0.050 pretravel inches and 0.219 overtravel inches and 0.002 differential inches and 0.008 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

0.500 amperes resistive dc and 20.000 amperes resistive ac

**Thread Series Designator:**

Unf

**Terminal Type And Quantity:**

2 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0