

View Online at <https://aerobasegroup.com/nsn/5930-01-129-1187>

Thread Class:

2a

Body Style:

Bushing/hole mounted

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.000 inches

Bushing Length:

0.530 inches

Body Length:

1.940 inches

Body Width:

0.687 inches

Body Height:

0.930 inches

Unthreaded Mounting Hole Diameter:

0.140 inches

Actuator Style:

Round

Actuator Diameter:

0.320 inches

Actuator Height:

1.099 inches

Actuator Free Position Height:

1.719 inches

Maximum Voltage Rating In Volts:

480.0 ac and 250.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing and unthreaded hole

Thread Size:

0.500 inches

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action single switch unit

Switch Release Force:

10.0 ounces

Switch Actuating Force:

Between 14.0 ounces and 22.0 ounces

Actuator Movement:

Between 0.050 pretravel inches and 0.219 overtravel inches and 0.002 differential inches and 0.008 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

0.500 amperes resistive dc and 20.000 amperes resistive ac

Thread Series Designator:

Unf

Terminal Type And Quantity:

2 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0