# NSN 5930-01-129-1359

Pressure Switch - Page 1 of 2



<u> </u>
View Online at https://aerobasegroup.com/nsn/5930-01-129-1359
Overall Length:
5.125 inches
Overall Height:
2.875 inches
Overall Width:
4.938 inches
Body Length:
2.750 inches
Unthreaded Mounting Hole Diameter:
0.281 inches
Longest Horizontal Distance Between Mounting Centers:
2.406 inches
Shortest Horizontal Distance Between Mounting Centers:
0.656 inches
Longest Vertical Distance Between Mounting Centers:
3.281 inches
Pressure Switch Type:
Gage
Mounting Method:
Bracket and unthreaded hole
Features Provided:
Electrical access port
Thready Qty Per Inch (tpi):
18 single pressure connection
Contact Action Stimulus:
Increase
Thread Size:
0.375 inches single pressure connection
Mounting Facility Pattern:
Isosceles triangle
Nonpile-up Contact Arrangement:
2 pole, double throw, double break/double make, one position momentary
Terminal Type:

Screw

#### **Contact Load Current Rating:**

9.6 amperes resistive load fourth voltage

## **Contact Adjustability:**

Deactuation point adjustable and actuation point adjustable

#### **Contact Adjustment Range:**

+15.00/+50.00 actuation point pound and +15.00/+50.00 deactuation point pound

#### **Contact Adjustment Type:**

External deactuation point screw and external actuation point screw

# NSN 5930-01-129-1359

Pressure Switch - Page 2 of 2



### **Contact Voltage Rating In Volts:**

550.0 dc at sea level third voltage

#### **Pressure Connector Type:**

Plain, threaded internal single connection

Media For Which Designed:

Gas or liquid

### **Thread Series Designator:**

Npt single pressure connection

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A048b0