NSN 5930-01-129-4154

Pressure Switch - Page 1 of 2



- 1000a.0 G.m.c 1 ago 1 0/ 2
View Online at https://aerobasegroup.com/nsn/5930-01-129-4154
Thread Class:
3a all pressure connection
Overall Length:
2.260 inches
Overall Height:
3.317 inches
Body Diameter:
1.600 inches
End Application:
An/bqq-5b
Pressure Switch Type:
Differential
Operating Tempurature Rating:
Between 36.0 degrees fahrenheit and 100.0 degrees fahrenheit
Mounting Method:
Inlet connection and outlet connection
Features Provided:
Hermetically sealed case
Thready Qty Per Inch (tpi):
20 all pressure connection
Contact Action Stimulus:
Increase
Proof Pressure:
225.00 pounds per square inch
Thread Size:
0.438 inches single pressure connection
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary

Sensing Element Burst Pressure:

375.00 pounds per square inch

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

600.0 milliamperes resistive load single voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

2.00 actuation point pounds per square inch and 0.30 differential point pounds per square inch

Contact Voltage Rating In Volts:

30.0 dc at sea level single voltage

Pressure Connector Type:

Flared, threaded external all connections

NSN 5930-01-129-4154Pressure Switch - Page 2 of 2



Media For Which Designed:	
Liquid	
Thread Series Designator:	
Unf all pressure connection	
Shelf Life:	
N/a	
Unit Of Measure:	

Demilitarization:

No

Fiig:

A048b0