

View Online at <https://aerobasegroup.com/nsn/5930-01-129-4552>

Overall Length:

Between 1.074 inches and 1.206 inches

Overall Height:

0.500 inches

Body Diameter:

0.642 inches

Body Height:

Between 0.280 inches and 0.395 inches

Unthreaded Mounting Hole Diameter:

Between 0.113 inches and 0.121 inches

Distance Between Mounting Facility Centers:

Between 0.807 inches and 0.815 inches

Temperature Sensing Element Type:

Disc

Operating Temperature Rating:

Between -65.0 degrees fahrenheit and 500.0 degrees fahrenheit

Mounting Method:

Bracket and unthreaded hole

Features Provided:

Hermetically sealed case

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, single throw, normally closed, momentary action

Terminal Type:

Tab, solder lug

Contact Load Current Rating:

5.0 amperes resistive load second voltage and 2.5 amperes inductive load second voltage and 1.0 amperes lamp load second voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

243.00 actuation point degrees fahrenheit and 263.00 actuation point degrees fahrenheit and 215.00 deactuation point degrees fahrenheit and 231.00 deactuation point degrees fahrenheit

Contact Voltage Rating In Volts:

28.0 dc at sea level second voltage

Frequency In Hertz:

60.0 first voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Disc w/flange

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0