

View Online at <https://aerobasegroup.com/nsn/5930-01-129-5987>

**Thread Class:**

2a single threaded bushing

**Hazardous Locations/environmental Protection:**

Corrosion resistant and humidity resistant and salt spray resistant and vibration resistant and waterproof

**Overall Length:**

2.680 inches

**Body Diameter:**

0.780 inches

**Body Length:**

0.280 inches

**End Application:**

2350-01-087-1095

**Pressure Switch Type:**

Gage

**Width Across Flats:**

1.003 inches

**Operating Temperature Rating:**

Between -60.0 degrees fahrenheit and 350.0 degrees fahrenheit

**Mounting Method:**

Threaded bushing

**Features Provided:**

Hermetically sealed case

**Contact Action Stimulus:**

Increase

**Proof Pressure:**

800.00 pounds per square inch gage

**Thread Size:**

0.750 inches single threaded bushing

**Nonpile-up Contact Arrangement:**

1 pole, single throw, normally closed, momentary action

**Terminal Type:**

Connector, receptacle

**Contact Load Current Rating:**

1.0 amperes resistive load single voltage

**Contact Adjustability:**

Actuation point not adjustable

**Contact Stimulus Rating:**

100.00 actuation point pounds per square inch gage and 400.00 actuation point pounds per square inch gage

**Contact Voltage Rating In Volts:**

28.0 dc at sea level single voltage

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Cylindrical w/flange

**Thread Series Designator:**

Unf single threaded bushing

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0