

View Online at <https://aerobasegroup.com/nsn/5930-01-129-5987>

Thread Class:

2a single threaded bushing

Hazardous Locations/environmental Protection:

Corrosion resistant and humidity resistant and salt spray resistant and vibration resistant and waterproof

Overall Length:

2.680 inches

Body Diameter:

0.780 inches

Body Length:

0.280 inches

End Application:

2350-01-087-1095

Pressure Switch Type:

Gage

Width Across Flats:

1.003 inches

Operating Temperature Rating:

Between -60.0 degrees fahrenheit and 350.0 degrees fahrenheit

Mounting Method:

Threaded bushing

Features Provided:

Hermetically sealed case

Contact Action Stimulus:

Increase

Proof Pressure:

800.00 pounds per square inch gage

Thread Size:

0.750 inches single threaded bushing

Nonpile-up Contact Arrangement:

1 pole, single throw, normally closed, momentary action

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

1.0 amperes resistive load single voltage

Contact Adjustability:

Actuation point not adjustable

Contact Stimulus Rating:

100.00 actuation point pounds per square inch gage and 400.00 actuation point pounds per square inch gage

Contact Voltage Rating In Volts:

28.0 dc at sea level single voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Cylindrical w/flange

Thread Series Designator:

Unf single threaded bushing

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0