

View Online at <https://aerobasegroup.com/nsn/5930-01-129-7675>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Watertight

Overall Length:

5.219 inches

Overall Height:

1.781 inches

Overall Width:

1.656 inches

Actuator Length:

1.875 inches

Actuator Style:

Roller arm

Actuator Roller Diameter:

0.750 inches

Actuator Roller Width:

0.281 inches

Housing Height:

1.781 inches

Housing Length:

2.844 inches

Housing Width:

1.656 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Length:

2.344 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Width:

1.156 inches

Maximum Voltage Rating In Volts:

440.0 ac and 230.0 dc

End Application:

Casrep items

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Features Provided:

Actuator seal

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Actuating Force:

32.0 ounces

Actuator Movement:

4.0 pretravel degrees and 10.0 overtravel degrees

Contact Load Current Rating At Maximum Rated Voltage:

200.000 milliamperes resistive dc and 6.000 amperes resistive ac

Terminal Type And Quantity:

3 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0