

View Online at <https://aerobasegroup.com/nsn/5930-01-129-9293>

**Body Style:**

Bushing mounted

**Hazardous Locations/environmental Protection:**

Dustproof

**Body Diameter:**

0.720 inches

**Bushing Length:**

0.625 inches

**Body Length:**

1.000 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.250 inches

**Actuator Free Position Height:**

0.875 inches

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**End Application:**

Inflight test

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thread Size:**

0.625 inches

**Nonpile-up Contact Arrangement:**

2 pole, double throw, both positions maintained single switch unit

**Switch Release Force:**

32.0 inch-ounces

**Switch Actuating Force:**

96.0 inch-ounces

**Actuator Movement:**

0.875 pretravel inches and 0.240 overtravel inches and 0.020 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 3.000 amperes inductive dc and 4.000 amperes motor dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac

**Thread Series Designator:**

Unef

**Terminal Type And Quantity:**

6 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0