NSN 5930-01-129-9445

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-129-9445

Between 1.465 inches and 1.510 inches

Overall Height:

0.360 inches

Body Diameter:

0.660 inches

Mounting Slot Width:

0.104 inches

Body Height:

0.300 inches

Distance Between Mounting Facility Centers:

Between 0.937 inches and 0.999 inches

Tempurature Sensing Element Type:

Internal sensor

Operating Tempurature Rating:

Between -10.0 degrees fahrenheit and 400.0 degrees fahrenheit

Mounting Method:

Bracket and slot

Features Provided:

Hermetically sealed case

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Terminal Type:

Tab, solder lug

Contact Load Current Rating:

2.0 amperes resistive load second voltage and 1.0 amperes inductive load second voltage and 1.0 amperes lamp load second voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

175.00 actuation point degrees fahrenheit and 170.00 deactuation point degrees fahrenheit and 173.00 deactuation point degrees fahrenheit and 2.00 differential point degrees fahrenheit and 5.00 differential point degrees fahrenheit

Contact Voltage Rating In Volts:

28.0 dc at sea level second voltage

Special Features:

Terminals at right angle degree

Frequency In Hertz:

60.0 first voltage

Media For Which Designed:

Gas or liquid

NSN 5930-01-129-9445

Thermostatic Switch - Page 2 of 2



| Style Designator: | Style | Design | ator: |
|-------------------|-------|--------|-------|
|-------------------|-------|--------|-------|

Disc w/flange

Test Data Document:

81349-mil-s-24236 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-s-24236/20 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0