## NSN 5930-01-130-1838

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-130-1838

Body Style:
Hole mount
Hazardous Locations/environmental Protection:
Watertight
Overall Length:
3.680 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
3.000 inches
Overall Height:
8.000 inches
Overall Width:
3.750 inches
Body Width:
3.750 inches
Body Height:
8.000 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
7.250 inches
Switch Actuator Quantity:
3
Actuator Style:
Round, flush
Actuator Color:
Red 3rd actuator
Actuator Inscription:
Send 2nd actuator
Maximum Voltage Rating In Volts:
440.0 ac and 355.0 dc
End Application:
Casrep items
Inclosure Type:
Fully enclosed
Mounting Method:
Threaded bushing
Features Provided:
Actuator seal
Nonpile-up Contact Arrangement:
3 two circuit, double break/double make, both positions maintained single switch unit
Contact Load Current Rating At Maximum Rated Voltage:
500.000 milliamperes resistive dc and 5.000 amperes resistive ac
Terminal Type And Quantity:

16 screw

## NSN 5930-01-130-1838

Push Switch - Page 2 of 2



-				
٠.	hΔ	Iŧ.	ife:	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0