

View Online at <https://aerobasegroup.com/nsn/5930-01-130-8491>

**Thread Class:**

2a

**Body Style:**

Bushing mounted

**Hazardous Locations/environmental Protection:**

Dustproof

**Overall Length:**

2.375 inches

**Overall Height:**

Between 0.625 inches and 0.720 inches

**Overall Width:**

Between 0.625 inches and 0.720 inches

**Body Diameter:**

Between 0.625 inches and 0.720 inches

**Bushing Length:**

1.000 inches

**Body Length:**

1.000 inches

**Case Material:**

Plastic

**Actuator Style:**

Round

**Actuator Diameter:**

0.250 inches

**Actuator Height:**

0.375 inches

**Actuator Free Position Height:**

1.375 inches

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**End Application:**

Fuselage

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Features Provided:**

Actuator seal

**Thread Size:**

0.625 inches

**Nonpile-up Contact Arrangement:**

2 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

64.0 ounces

**Switch Actuating Force:**

144.0 ounces

**Actuator Movement:**

Between 0.050 pretravel inches and 0.250 overtravel inches and 0.030 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 3.000 amperes inductive dc and 1.000 amperes lamp dc and 4.000 amperes motor dc and 1.000 amperes resistive ac and 1.000 amperes inductive ac and 1.000 amperes lamp ac and 1.000 amperes motor ac

**Precious Material And Location:**

Contact surfaces gold

**Thread Series Designator:**

Unef

**Terminal Type And Quantity:**

6 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0