

View Online at <https://aerobasegroup.com/nsn/5930-01-130-9151>

Hazardous Locations/environmental Protection:

Explosion proof

Overall Length:

6.408 inches

Overall Height:

3.300 inches

Overall Width:

4.750 inches

Body Length:

0.850 inches

Unthreaded Mounting Hole Diameter:

0.265 inches

Distance Between Mounting Facility Centers:

4.250 inches

Capillary Tube Length:

5.558 inches

End Application:

Multi-hull

Temperature Sensing Element Type:

Capillary tube

Operating Temperature Rating:

300.00 degrees fahrenheit

Mounting Method:

Unthreaded hole

Features Provided:

Hermetically sealed case

Contact Action Stimulus:

Decrease

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained

Terminal Type:

Wire lead

Contact Load Current Rating:

400.0 milliamperes resistive load second voltage and 200.0 milliamperes inductive load second voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+95.00/+215.00 actuation point degrees fahrenheit and +80.00/+210.00 deactuation point degrees fahrenheit

Contact Adjustment Type:

External deactuation point screw and external actuation point screw

Contact Voltage Rating In Volts:

480.0 ac at sea level first voltage

Frequency In Hertz:

60.0 first voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0