

View Online at <https://aerobasegroup.com/nsn/5930-01-130-9156>

**Body Style:**

Panel mount

**Hazardous Locations/environmental Protection:**

Moisture proof

**Body Length:**

3.060 inches

**Body Width:**

0.740 inches

**Body Height:**

0.740 inches

**Case Material:**

Metal

**Actuator Length:**

0.730 inches

**Actuator Style:**

Rectangular

**Actuator Width:**

0.730 inches

**Illuminated Actuator Color:**

White single actuator

**Actuator Inscription:**

Spare single actuator

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**End Application:**

Multi-hull

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Panel

**Features Provided:**

Rfi shielding

**Nonpile-up Contact Arrangement:**

4 pole, double throw, two positions momentary single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 2.500 amperes inductive dc and 1.500 amperes lamp dc and 5.000 amperes resistive ac and 2.500 amperes inductive ac and 1.500 amperes lamp ac

**Precious Material And Location:**

Contact surface gold

**Terminal Type And Quantity:**

16 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0