

View Online at <https://aerobasegroup.com/nsn/5930-01-130-9156>

Body Style:

Panel mount

Hazardous Locations/environmental Protection:

Moisture proof

Body Length:

3.060 inches

Body Width:

0.740 inches

Body Height:

0.740 inches

Case Material:

Metal

Actuator Length:

0.730 inches

Actuator Style:

Rectangular

Actuator Width:

0.730 inches

Illuminated Actuator Color:

White single actuator

Actuator Inscription:

Spare single actuator

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

End Application:

Multi-hull

Inclosure Type:

Fully enclosed

Mounting Method:

Panel

Features Provided:

Rfi shielding

Nonpile-up Contact Arrangement:

4 pole, double throw, two positions momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 2.500 amperes inductive dc and 1.500 amperes lamp dc and 5.000 amperes resistive ac and 2.500 amperes inductive ac and 1.500 amperes lamp ac

Precious Material And Location:

Contact surface gold

Terminal Type And Quantity:

16 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0