

View Online at <https://aerobasegroup.com/nsn/5930-01-131-0233>

Thread Class:

2a single mounting facility

Thread Length:

0.437 inches single mounting facility

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

1.899 inches

First Flat Length:

0.250 inches single actuator

Flat Height:

0.216 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.874 inches single actuator

Overall Diameter:

Between 1.000 inches and 1.306 inches

Nonturn Device Radius:

0.375 inches at 3:00 o'clock

Individual Section Quantity:

1

Nonturn Device Type:

Tab at 3:00 o'clock

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 single section front

Throw Quantity:

10 single section front

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Switch Actuator Indexing Position Quantity:

10 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Makes before breaks single section front

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

750.0 milliamperes resistive load ac at sea level

Style Designator:

Tap, circular, bushing mount

Test Data Document:

81349-mil-s-3786 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unef single mounting facility

Specification Data:

81349-mil-s-3786/4 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0