

View Online at <https://aerobasegroup.com/nsn/5930-01-131-3806>

Thread Class:

2b single pressure connection

Inside Diameter:

0.500 inches single connection

Overall Length:

3.500 inches

Overall Height:

7.000 inches

Overall Width:

2.500 inches

Body Height:

3.250 inches

Unthreaded Mounting Hole Diameter:

0.266 inches

Longest Horizontal Distance Between Mounting Centers:

2.719 inches

Longest Vertical Distance Between Mounting Centers:

2.719 inches

End Application:

F16oprtalfltt

Pressure Switch Type:

Differential

Mounting Method:

Unthreaded hole

Thready Qty Per Inch (tpi):

14 single pressure connection

Contact Action Stimulus:

Increase

Thread Size:

0.500 inches single pressure connection

Mounting Facility Pattern:

Two position diagonal

Nonpile-up Contact Arrangement:

2 two circuit, double break/double make, one position momentary

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

6.0 amperes resistive load second voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+0.00/+75.00 actuation point pounds per square inch and +6.00/+90.00 deactuation point pounds per square inch

Contact Adjustment Type:

External deactuation point screw and external actuation point screw

Contact Voltage Rating In Volts:

600.0 ac at sea level first voltage

Pressure Connector Type:

Plain, threaded internal single connection

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular

Thread Series Designator:

Nptf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0