NSN 5930-01-131-8008

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-131-8008

Thread Class:						
3a single threaded bushing						
Overall Length:						
2.438 inches						
Body Diameter:						
0.312 inches						
Body Length:						
1.094 inches						
End Application:						
2305-01-061-6230						
Tempurature Sensing Element Type:						
Immersion well						
Width Across Flats:						
0.750 inches						
Mounting Method:						
Threaded bushing						
Thready Qty Per Inch (tpi):						
20 single threaded bushing						
Contact Action Stimulus:						
Increase						
Thread Size:						
0.500 inches single threaded bushing						
Nonpile-up Contact Arrangement:						
1 pole, single throw, normally open, momentary action						
Terminal Type:						
Connector, receptacle						
Contact Load Current Rating:						
2.0 amperes resistive load second voltage and 0.5 amperes inductive load second voltage						
Contact Adjustability:						
Deactuation point not adjustable and actuation point not adjustable						
Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating:						
Contact Stimulus Rating:						
Contact Stimulus Rating: 246.00 actuation point degrees fahrenheit and 241.00 deactuation point degrees fahrenheit						
Contact Stimulus Rating: 246.00 actuation point degrees fahrenheit and 241.00 deactuation point degrees fahrenheit Contact Voltage Rating In Volts:						
Contact Stimulus Rating: 246.00 actuation point degrees fahrenheit and 241.00 deactuation point degrees fahrenheit Contact Voltage Rating In Volts: 28.0 dc at sea level second voltage						
Contact Stimulus Rating: 246.00 actuation point degrees fahrenheit and 241.00 deactuation point degrees fahrenheit Contact Voltage Rating In Volts: 28.0 dc at sea level second voltage Media For Which Designed:						
Contact Stimulus Rating: 246.00 actuation point degrees fahrenheit and 241.00 deactuation point degrees fahrenheit Contact Voltage Rating In Volts: 28.0 dc at sea level second voltage Media For Which Designed: Gas or liquid						
Contact Stimulus Rating: 246.00 actuation point degrees fahrenheit and 241.00 deactuation point degrees fahrenheit Contact Voltage Rating In Volts: 28.0 dc at sea level second voltage Media For Which Designed: Gas or liquid Style Designator:						
Contact Stimulus Rating: 246.00 actuation point degrees fahrenheit and 241.00 deactuation point degrees fahrenheit Contact Voltage Rating In Volts: 28.0 dc at sea level second voltage Media For Which Designed: Gas or liquid Style Designator: Cylindrical w/flange						

N/a

NSN 5930-01-131-8008

Thermostatic Switch - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A048b0