## NSN 5930-01-131-8777

**Hazardous Locations/environmental Protection:** 

Push Switch - Page 1 of 2

**Body Style:**Panel mounted



View Online at https://aerobasegroup.com/nsn/5930-01-131-8777

Explosion proof
Overall Length:
2.750 inches
Overall Height:
0.688 inches
Overall Width:
0.688 inches
Body Width:
0.688 inches
Body Height:
0.688 inches
Case Material:
Metal
Actuator Length:
0.620 inches
Actuator Style:
Rectangular
Actuator Height:
0.070 inches
Actuator Width:
0.620 inches
Actuator Color:
Amber single actuator and green single actuator
Illuminated Actuator Color:
Amber single actuator and green single actuator
Actuator Inscription:
Adf single actuator
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Mounting Surface To Terminal End Distance:
2.620 inches
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Features Provided:
Rfi shielding
Nonpile-up Contact Arrangement:
2 pole, double throw, both positions maintained single switch unit

## NSN 5930-01-131-8777

Push Switch - Page 2 of 2



## **Contact Load Current Rating At Maximum Rated Voltage:**

7.000 amperes resistive dc and 4.000 amperes inductive dc and 2.500 amperes lamp dc and 7.000 amperes resistive ac and 7.000 amperes inductive ac and 2.000 amperes lamp ac

P	racions	Matarial	And	Location:
_	recious	wateriai	Allu	LOCALION.

Contacts silver

**Terminal Type And Quantity:** 

6 turret and 5 tab, solder lug

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0