# NSN 5930-01-131-8782

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-131-8782

Body Style:
Panel mounted
Hazardous Locations/environmental Protection:
Explosion proof
Overall Length:
2.750 inches
Overall Height:
2.750 inches
Overall Width:
0.688 inches
Body Width:
0.688 inches
Body Height:
0.688 inches
Case Material:
Metal
Actuator Length:
0.620 inches
Actuator Style:
Rectangular
Actuator Height:
0.070 inches
Actuator Width:
0.620 inches
Actuator Color:
Amber single actuator and green single actuator
Illuminated Actuator Color:
Amber single actuator and green single actuator
Actuator Inscription:
Hf-1 single actuator
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Mounting Surface To Terminal End Distance:
2.620 inches
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Features Provided:
Rfi shielding
Nonpile-up Contact Arrangement:
2 pole, double throw, one position momentary single switch unit

## NSN 5930-01-131-8782

Push Switch - Page 2 of 2



Afve

### **Contact Load Current Rating At Maximum Rated Voltage:**

7.000 amperes resistive dc and 4.000 amperes inductive dc and 2.500 amperes lamp dc and 7.000 amperes resistive ac and 7.000 amperes inductive ac and 2.000 amperes lamp ac

### **Precious Material And Location:**

Contacts silver

### **Terminal Type And Quantity:**

6 turret and 5 tab, solder lug

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0