NSN 5930-01-131-8783

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-131-8783

Body Style:		
Panel mounted		
Hazardous Locations/environmental Protection:		
Explosion proof		
Overall Length:		
2.750 inches		
Overall Height:		
0.688 inches		
Overall Width:		
0.688 inches		
Body Width:		
0.688 inches		
Body Height:		
0.688 inches		
Case Material:		
Metal		
Actuator Length:		
0.620 inches		
Actuator Style:		
Rectangular		
Actuator Height:		
0.070 inches		
Actuator Width:		
0.620 inches		
Actuator Color:		
Amber single actuator and green single actuator		
Illuminated Actuator Color:		
Amber single actuator and green single actuator		
Actuator Inscription:		
lcs single actuator		
Maximum Voltage Rating In Volts:		
115.0 ac and 28.0 dc		
Mounting Surface To Terminal End Distance:		
2.620 inches		
Inclosure Type:		
Fully enclosed		
Mounting Method:		
Panel		
Features Provided:		
Rfi shielding		
Nonpile-up Contact Arrangement:		
2 pole, double throw, one position momentary single switch unit		

NSN 5930-01-131-8783

Push Switch - Page 2 of 2



`riticalit\	Code Justification	٠-
Jiilleanii	Code Justilication	ı.

Afve

Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 4.000 amperes inductive dc and 2.500 amperes lamp dc and 7.000 amperes resistive ac and 7.000 amperes inductive ac and 2.000 amperes lamp ac

Precious Material And Location:

Contacts silver

Terminal Type And Quantity:

6 turret and 5 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0