NSN 5930-01-132-1606

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-132-1606

Thread Class:

2a single mounting facility

Thread Length:

0.250 inches single mounting facility

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

1.640 inches

Shaft Diameter:

0.125 inches single actuator

Shaft Length:

1.000 inches single actuator

Overall Diameter:

0.500 inches

Individual Section Quantity:

1

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

3 single section front

Throw Quantity:

3 single section front

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.250 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Switch Actuator Indexing Position Quantity:

3 single actuator

Shaft Type:

Round single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes single section front

Switch Actuator Positioning Increment:

36.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

100.0 milliamperes resistive load dc at sea level

NSN 5930-01-132-1606

Rotary Switch - Page 2 of 2



Precious Material And Location:
Contacts silver
Precious Material:
Silver
Style Designator:
Snap or line
Thread Series Designator:
Unf single mounting facility
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A052b0