

View Online at <https://aerobasegroup.com/nsn/5930-01-132-3062>

**Thread Class:**

2b single pressure connection

**Inside Diameter:**

0.438 inches single connection

**Hazardous Locations/environmental Protection:**

Waterproof

**Overall Length:**

1.976 inches

**Body Length:**

1.876 inches

**Overall Diameter:**

0.813 inches

**Pressure Switch Type:**

Gage

**Width Across Flats:**

0.563 inches

**Operating Temperature Rating:**

Between -20.0 degrees fahrenheit and 150.0 degrees fahrenheit

**Mounting Method:**

Line

**Contact Action Stimulus:**

Increase

**Proof Pressure:**

400.00 pounds per square inch gage

**Thread Size:**

0.438 inches single pressure connection

**Nonpile-up Contact Arrangement:**

1 pole, single throw, normally open, momentary action

**Terminal Type:**

Wire lead

**Contact Load Current Rating:**

2.0 amperes resistive load third voltage

**Contact Adjustability:**

Actuation point not adjustable and deactuation point not adjustable

**Contact Stimulus Rating:**

30.00 actuation point pounds per square inch gage and 10.00 deactuation point pounds per square inch gage

**Contact Voltage Rating In Volts:**

28.0 dc at sea level fourth voltage

**Pressure Connector Type:**

Swivel nut, flare, threaded internal single connection

**Frequency In Hertz:**

60.0 third voltage

**Media For Which Designed:**

Gas

**Style Designator:**

Cylindrical

**Thread Series Designator:**

Unf single pressure connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0