NSN 5930-01-132-3062

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-132-3062

View Online at https://aerobasegroup.com/nsn/5930-01-132-3062
Thread Class:
2b single pressure connection
Inside Diameter:
0.438 inches single connection
Hazardous Locations/environmental Protection:
Waterproof
Overall Length:
1.976 inches
Body Length:
1.876 inches
Overall Diameter:
0.813 inches
Pressure Switch Type:
Gage
Width Across Flats:
0.563 inches
Operating Tempurature Rating:
Between -20.0 degrees fahrenheit and 150.0 degrees fahrenheit
Mounting Method:
Line
Contact Action Stimulus:
Increase
Proof Pressure:
400.00 pounds per square inch gage
Thread Size:
0.438 inches single pressure connection
Nonpile-up Contact Arrangement:
1 pole, single throw, normally open, momentary action
Terminal Type:
Wire lead
Contact Load Current Rating:
2.0 amperes resistive load third voltage
Contact Adjustability:
Actuation point not adjustable and deactuation point not adjustable
Contact Stimulus Rating:
30.00 actuation point pounds per square inch gage and 10.00 deactuation point pounds per square inch gage
Contact Voltage Rating In Volts:
28.0 dc at sea level fourth voltage
Pressure Connector Type:
Swivel nut, flare, threaded internal single connection

Frequency In Hertz:

60.0 third voltage

NSN 5930-01-132-3062Pressure Switch - Page 2 of 2



Media For Which Designed:
Gas
Style Designator:
Cylindrical
Thread Series Designator:
Unf single pressure connection
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A048b0