# NSN 5930-01-132-5790

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-132-5790

### **Thread Class:**

2a single mounting facility

### Thread Length:

0.437 inches single mounting facility

## **Overall Length:**

2.300 inches

#### First Flat Length:

0.250 inches single actuator

#### Flat Height:

0.219 inches single actuator

#### Shaft Diameter:

0.250 inches single actuator

#### Shaft Length:

0.437 inches single actuator

#### **Overall Diameter:**

1.162 inches

#### Individual Section Quantity:

2

#### Switch Contact Basic Design:

Nonpile-up symmetrical

#### **Pole Quantity:**

3 single section in-line

#### **Throw Quantity:**

3 single section in-line

#### **Mounting Method:**

Threaded bushing w/panel seal single mounting facility

#### Thready Qty Per Inch (tpi):

32 single mounting facility

#### Thread Size:

0.375 inches single mounting facility

#### Contact Voltage Rating In Volts:

115.0 ac at sea level

#### Switch Actuator Indexing Position Quantity:

3 single actuator

#### Shaft Type:

Round, flatted single actuator

### **Terminal Type:**

Tab, solder lug

#### **Contact Switching Action:**

Breaks before makes single section in-line

# Switch Actuator Stop Device Type:

Fixed-adjustable stops single actuator

# NSN 5930-01-132-5790

Rotary Switch - Page 2 of 2



**Contact Load Current Rating:** 

1.5 amperes resistive load ac at sea level

Style Designator:

Tap, circular, bushing mount

**Thread Series Designator:** 

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A052b0