## NSN 5930-01-132-6098

6.00 differential point pounds per square inch

Contact Voltage Rating In Volts: 480.0 ac at sea level first voltage

Pressure Switch - Page 1 of 2

Overall Length: 8.000 inches Overall Height: 3.300 inches



View Online at https://aerobasegroup.com/nsn/5930-01-132-6098

Overall Width:
4.750 inches
Unthreaded Mounting Hole Diameter:
0.265 inches
Distance Between Mounting Facility Centers:
4.250 inches
Pressure Switch Type:
Gage
Operating Tempurature Rating:
Between -34.0 degrees celsius and 71.0 degrees celsius
Mounting Method:
Unthreaded hole
Thready Qty Per Inch (tpi):
18 single pressure connection
Contact Action Stimulus:
Increase
Proof Pressure:
4500.00 pounds per square inch
Thread Size:
0.250 inches single pressure connection
Mounting Facility Pattern:
Two position in-line
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary
Terminal Type:
Wire lead
Contact Load Current Rating:
400.0 milliamperes resistive load third voltage and 200.0 milliamperes inductive load third voltage
Contact Adjustability:
Actuation point adjustable
Contact Adjustment Range:
+30.00/+100.00 actuation point pounds per square inch
Contact Adjustment Type:
Internal actuation point serrated nut
Contact Stimulus Rating:

## NSN 5930-01-132-6098

Pressure Switch - Page 2 of 2



Press	ure Connector	туре
Plain.	threaded intern	al sin

lain, threaded internal single connection

Frequency In Hertz:

50.0 second voltage and 60.0 second voltage

**Thread Series Designator:** 

Npt single pressure connection

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A048b0