

View Online at <https://aerobasegroup.com/nsn/5930-01-132-8306>

Body Style:

Hole mounted

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.281 inches

Body Length:

0.510 inches

Body Width:

0.156 inches

Body Height:

0.350 inches

Unthreaded Mounting Hole Diameter:

0.088 inches

Actuator Style:

Round

Actuator Diameter:

0.093 inches

Actuator Height:

0.065 inches

Actuator Free Position Height:

0.355 inches

Maximum Voltage Rating In Volts:

28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

1.5 ounces

Switch Actuating Force:

5.0 ounces

Actuator Movement:

0.035 pretravel inches and 0.006 overtravel inches and 0.015 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 3.000 amperes inductive dc and 1.000 amperes lamp dc

Precious Material And Location:

Contacts silver and contact and terminal surfaces gold

Terminal Type And Quantity:

3 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0