NSN 5930-01-132-8660

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-132-8660

3
Hazardous Locations/environmental Protection:
Watertight
Overall Length:
6.375 inches
Overall Height:
4.500 inches
Overall Width:
2.625 inches
Shaft Diameter:
0.500 inches single actuator
Shaft Length:
1.500 inches single actuator
Unthreaded Mounting Hole Diameter:
0.219 inches single mounting facility
Individual Section Quantity:
1
Longest Horizontal Distance Between Mounting Centers:
6.375 inches single mounting facility
Longest Vertical Distance Between Mounting Centers:
4.000 inches single mounting facility
End Application:
1935-00-264-6219
Switch Contact Basic Design:
Nonpile-up nonsymmetrical
Mounting Method:
Base single mounting facility and unthreaded hole single mounting facility
Features Provided:
Metallic inclosure and cam actuated
Contact Voltage Rating In Volts:
600.0 highest ac voltage rating at sea level
Mounting Facility Pattern:
Four position rectangular single mounting facility
Shaft Type:
Round single actuator
Contact Switching Action:
Breaks before makes single section in-line
Contact Load Current Rating:
40.0 amperes resistive load lowest ac voltage rating at sea level
Style Designator:
In-line, cam actuated
Shelf Life:

N/a

NSN 5930-01-132-8660Rotary Switch - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

Demilitarization:

No

Fiig:

A052b0