

View Online at <https://aerobasegroup.com/nsn/5930-01-132-8666>

Body Style:

Bushing mount

Overall Length:

0.450 inches

Overall Height:

1.695 inches

Overall Width:

0.500 inches

Bushing Length:

0.350 inches

Body Length:

0.450 inches

Body Width:

0.500 inches

Body Height:

0.410 inches

Case Material:

Plastic

Actuator Style:

Rectangular

Actuator Height:

0.840 inches

Actuator Width:

0.100 inches

Actuator Position-action Relationship:

Up position momentary and down position momentary and center position maintained

Maximum Voltage Rating In Volts:

250.0 ac and 28.0 dc

End Application:

4920nc793148p

Mounting Surface To Terminal End Distance:

0.505 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

40

Thread Size:

0.250 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, two positions momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 2.000 amperes resistive ac

Precious Material And Location:

Terminal surfaces and contacts silver

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0