NSN 5930-01-133-3672

Thermostatic Switch - Page 1 of 2

Gas or liquid



View Online at https://aerobasegroup.com/nsn/5930-01-133-3672

Overall Length:
5.188 inches
Overall Width:
2.812 inches
Body Height:
2.750 inches
Unthreaded Mounting Hole Diameter:
0.281 inches
Longest Horizontal Distance Between Mounting Centers:
2.406 inches
Shortest Horizontal Distance Between Mounting Centers:
0.656 inches
Longest Vertical Distance Between Mounting Centers:
3.281 inches
End Application:
Electric plan
Tempurature Sensing Element Type:
Bulb
Mounting Method:
Bracket and unthreaded hole
Features Provided:
Electrical access port
Contact Action Stimulus:
Increase
Mounting Facility Pattern:
Isosceles triangle
Nonpile-up Contact Arrangement:
2 pole, double throw, double break/double make, permanent jumper, one position momentary
Terminal Type:
Screw
Contact Load Current Rating:
9.6 amperes inductive load fourth voltage
Contact Adjustability:
Deactuation point adjustable and actuation point adjustable
Contact Adjustment Range:
+90.00/+165.00 actuation point degrees fahrenheit and +90.00/+165.00 deactuation point degrees fahrenheit
Contact Adjustment Type:
External deactuation point screw and external actuation point screw
Contact Voltage Rating In Volts:
550.0 dc at sea level third voltage
Media For Which Designed:

NSN 5930-01-133-3672

Thermostatic Switch - Page 2 of 2



_					
•	n	0 1	•	12	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0