NSN 5930-01-133-3673

Thermostatic Switch - Page 1 of 2

Overall Length:



View Online at https://aerobasegroup.com/nsn/5930-01-133-3673

5.188 inches
Overall Width:
2.812 inches
Body Height:
2.750 inches
Unthreaded Mounting Hole Diameter:
0.281 inches
Capillary Tube Length:
480.0 inches
Bulb Length:
6.500 inches
Bulb Diameter:
1.125 inches
Longest Horizontal Distance Between Mounting Centers:
2.406 inches
Shortest Horizontal Distance Between Mounting Centers:
0.656 inches
Longest Vertical Distance Between Mounting Centers:
3.281 inches
End Application:
Electric plan
Tempurature Sensing Element Type:
Capillary tube-bulb
Mounting Method:
Bracket and unthreaded hole
Features Provided:
Electrical access port
Contact Action Stimulus:
Increase
Mounting Facility Pattern:
Isosceles triangle
Nonpile-up Contact Arrangement:
1 pole, single throw, normally open, momentary action
Terminal Type:
Screw
Contact Load Current Rating:
9.6 amperes inductive load fourth voltage

Contact Adjustment Range:

Deactuation point adjustable and actuation point adjustable

Contact Adjustability:

+60.00/+130.00 actuation point degrees fahrenheit and +60.00/+130.00 deactuation point degrees fahrenheit

NSN 5930-01-133-3673

Thermostatic Switch - Page 2 of 2



Contact Adjustment Type	/pe
-------------------------	-----

External deactuation point screw and external actuation point screw

Contact Voltage Rating In Volts:

550.0 dc at sea level third voltage

Media For Which Designed:

Gas or liquid

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0