

View Online at <https://aerobasegroup.com/nsn/5930-01-133-5078>

**Body Style:**

Hole mounted

**Hazardous Locations/environmental Protection:**

Waterproof

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

6.000 inches

**Body Length:**

7.970 inches

**Body Width:**

6.750 inches

**Body Height:**

4.470 inches

**Unthreaded Mounting Hole Diameter:**

0.410 inches

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

5.500 inches

**Actuator Length:**

3.500 inches

**Actuator Style:**

Leaf

**Actuator Width:**

0.500 inches

**Actuator Position-action Relationship:**

Right position momentary and center position maintained and left position momentary

**Actuator Position-locking Relationship:**

Right position no locking action and center position no locking action and left position no locking action

**Maximum Voltage Rating In Volts:**

440.0 ac

**End Application:**

Used on boat davit assembly onboard 210 ft wmec and 378 whec c.G. Vessels

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Contact Load Current Rating At Maximum Rated Voltage:**

10.000 amperes resistive ac

**Terminal Type And Quantity:**

12 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0