NSN 5930-01-133-5708

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-133-5708

Body Style:			
Panel mounted			
Hazardous Locations/environmental Protection:			
Explosion proof and humidity resistant			
Overall Length:			
3.281 inches			
Overall Height:			
0.906 inches			
Overall Width:			
0.906 inches			
Body Width:			
0.750 inches			
Body Height:			
0.750 inches			
Actuator Length:			
0.620 inches			
Actuator Style:			
Rectangular			
Actuator Height:			
0.270 inches			
Actuator Width:			
0.620 inches			
Actuator Color:			
White single actuator and white single actuator			
Actuator Inscription:			
High/low single actuator			
Maximum Voltage Rating In Volts:			
120.0 ac			
Mounting Surface To Terminal End Distance:			
2.950 inches			
Inclosure Type:			
Fully enclosed			
Mounting Method:			
Panel			
Features Provided:			
Horizontal split lens			
Nonpile-up Contact Arrangement:			
3 two circuit, double break/double make, both positions maintained single switch unit			
Contact Load Current Rating At Maximum Rated Voltage:			
5.000 amperes resistive ac			

Special Features:

Horizontally split lens and legend

NSN 5930-01-133-5708

Push Switch - Page 2 of 2



Precious	Material	∆nd l	Location:
riecious	ivialeriai	Allu	LUCALIUII.

Terminals gold

Terminal Type And Quantity:

1 socket, integrated wire termination

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0