

View Online at <https://aerobasegroup.com/nsn/5930-01-133-7333>

Thread Class:

2a single mounting facility

Thread Length:

0.280 inches single mounting facility

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

1.665 inches

Shaft Diameter:

0.125 inches single actuator

Shaft Length:

0.720 inches single actuator

Overall Diameter:

0.524 inches

Individual Section Quantity:

1

Nonturn Device Type:

Flatted bushing at 3: 00 o'clock

Operating Temperature Range:

+0.0/+70.0 degrees celsius

End Application:

An/grc-212

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 single section rear

Throw Quantity:

10 single section rear

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.250 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Shaft Flat/slot Angular Location:

36.0 degrees from nonturn device single actuator

Switch Actuator Indexing Position Quantity:

10 single actuator

Shaft Type:

Round, slotted single actuator

Terminal Type:

Printed circuit

Contact Switching Action:

Breaks before makes single section rear

Switch Actuator Positioning Increment:

36.0 degrees single actuator

Detent Rotational Torque Range:

+8.000/+24.000 inch-ounces single actuator

Switch Actuator Stop Device Type:

Adjustable stop single actuator

Contact Load Current Rating:

200.0 milliamperes resistive load dc at sea level

Precious Material And Location:

Terminal surfaces gold

Precious Material:

Gold

Style Designator:

Snap or line

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0