## NSN 5930-01-134-3556

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-134-3556

| Body Style:  |
|--|
| Hole mounted   |
| Hazardous Locations/environmental Protection:  |
| Waterproof   |
| Overall Length:  |
| 2.435 inches   |
| Body Diameter:   |
| 0.810 inches   |
| Body Length:   |
| 0.380 inches   |
| Case Material:   |
| Metal  |
| Actuator Style:  |
| Round, flush   |
| Actuator Diameter:   |
| 0.438 inches   |
| Actuator Height:   |
| 0.032 inches   |
| Maximum Voltage Rating In Volts:   |
| 24.0 dc  |
| End Application:   |
| M60 tank family  |
| Inclosure Type:  |
| Fully enclosed   |
| Nonpile-up Contact Arrangement:  |
| 1 pole, single throw, both positions maintained single switch unit                       |
| Switch Release Force:  |
| 226.8 grams  |
| Switch Actuating Force:  |
| Between 453.6 grams and 907.2 grams  |
| Actuator Movement:   |
| Between 0.015 pretravel inches and 0.015 overtravel inches and 0.005 differential inches |
| Contact Load Current Rating At Maximum Rated Voltage:                                    |
| 15.000 amperes resistive dc and 7.500 amperes inductive dc and 7.500 amperes lamp dc     |
| Special Features:  |
| Cables 12.000 lg from switch   |
| Terminal Type And Quantity:  |
| 3 wire lead  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |

--

## NSN 5930-01-134-3556

Sensitive Switch - Page 2 of 2



Demilitarization:

No

Fiig:

A053a0