# NSN 5930-01-134-5171

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-134-5171

## **Thread Class:**

2a single mounting facility

## Thread Length:

0.375 inches single mounting facility

## **Overall Length:**

2.078 inches

### **Overall Height:**

2.312 inches

### **Overall Width:**

1.968 inches

#### Shaft Diameter:

0.250 inches single actuator

### Shaft Length:

0.375 inches single actuator

#### **Nonturn Device Radius:**

# 0.531 inches at 1: 30 o'clock

# Individual Section Quantity:

2

## Nonturn Device Type:

Tab at 1: 30 o'clock

## **Operating Tempurature Range:**

-65.0/+85.0 degrees celsius

# End Application:

Camera test s

## Switch Contact Basic Design:

Nonpile-up symmetrical

## Pole Quantity:

1 each section rear

## Throw Quantity:

22 each section rear

## **Mounting Method:**

Threaded bushing single mounting facility

## **Thread Size:**

0.375 inches single mounting facility

## Contact Voltage Rating In Volts:

28.0 dc at sea level

# Switch Actuator Indexing Position Quantity:

22 single actuator

#### Shaft Type:

Round single actuator

## **Terminal Type:**

Clip

# NSN 5930-01-134-5171

Rotary Switch - Page 2 of 2



Contact Switching Action:
Breaks before makes each section rear
Switch Actuator Positioning Increment:
15.0 degrees single actuator
Switch Actuator Stop Device Type:
Fixed stop single actuator
Contact Load Current Rating:
500.0 milliamperes resistive load dc at sea level and 50.0 milliamperes inductive load dc at sea level
Precious Material And Location:
Clips and rotor blade surfaces gold and clips and rotor blades silver
Precious Material:
Gold and silver
Style Designator:
Circular wafer, bushing mount
Thread Series Designator:
Unef single mounting facility
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A052b0