## NSN 5930-01-134-6220

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-134-6220

| Body Style:  |
|--|
| Hole mounted   |
| Center To Center Distance Between Mounting Facilities Parallel To Length:  |
| 1.000 inches   |
| Body Length:   |
| 1.940 inches   |
| Body Width:  |
| 0.687 inches   |
| Body Height:   |
| 1.040 inches   |
| Unthreaded Mounting Hole Diameter:   |
| Between 0.139 inches and 0.142 inches  |
| Actuator Length:   |
| 2.500 inches   |
| Actuator Style:  |
| Leaf   |
| Actuator Width:  |
| 0.190 inches   |
| Actuator Free Position Height:   |
| 1.078 inches   |
| Maximum Voltage Rating In Volts:   |
| 480.0 ac   |
| End Application:   |
| F/tf-15a acft  |
| Inclosure Type:  |
| Fully enclosed   |
| Mounting Method:   |
| Unthreaded hole  |
| Nonpile-up Contact Arrangement:  |
| 1 pole, double throw, one position momentary single switch unit  |
| Switch Release Force:  |
| 0.5 ounces   |
| Switch Actuating Force:  |
| 2.250 ounces   |
| Actuator Movement:   |
| Between 0.328 pretravel inches and 0.219 overtravel inches and 0.003 differential inches and 0.015 differential inches |
| Contact Load Current Rating At Maximum Rated Voltage:  |
| 15.000 amperes resistive ac  |
| Terminal Type And Quantity:  |
| 3 tab, solder lug  |
| Shelf Life:  |
| N/a  |

## NSN 5930-01-134-6220

Sensitive Switch - Page 2 of 2



|    | • • |             |     |     |      |
|----|-----|-------------|-----|-----|------|
| In | 18  | <i>(</i> )+ | МЛО | 201 | ure: |
|    |     |             |     |     |      |

--

Demilitarization:

Yes - demil/mli

Fiig:

A053a0