

View Online at <https://aerobasegroup.com/nsn/5930-01-135-0641>

Thread Class:

2a 2nd mounting facility

Thread Length:

0.250 inches 2nd mounting facility

Hazardous Locations/environmental Protection:

Shock resistant

Overall Length:

1.292 inches

First Flat Length:

0.250 inches single actuator

Flat Height:

0.094 inches single actuator

Shaft Diameter:

0.125 inches single actuator

Shaft Length:

0.375 inches single actuator

Overall Diameter:

0.562 inches

Individual Section Quantity:

1

Nonturn Device Type:

Flatted bushing at 3: 00 o'clock flatted bushing at 9: 00 o'clock

Operating Temperature Range:

-65.0/+85.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

2 single section rear

Throw Quantity:

7 single section rear

Mounting Method:

Printed circuit 1st mounting facility threaded bushing w/panel seal 2nd mounting facility

Thread Size:

0.250 inches 2nd mounting facility

Contact Voltage Rating In Volts:

115.0 ac at sea level 28.0 dc at sea level

Switch Actuator Indexing Position Quantity:

7 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Printed circuit

Contact Switching Action:

Breaks before makes single section rear

Switch Actuator Positioning Increment:

22.5 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

150.0 milliamperes resistive load ac at sea level 200.0 milliamperes resistive load dc at sea level

Precious Material And Location:

Contact and terminal surfaces gold

Precious Material:

Gold

Style Designator:

Snap or line

Thread Series Designator:

Unf 2nd mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0