

View Online at <https://aerobasegroup.com/nsn/5930-01-135-2047>

**Body Style:**

Panel mount

**Hazardous Locations/environmental Protection:**

Moisture proof and shock proof

**Overall Length:**

0.755 inches

**Overall Height:**

3.060 inches

**Overall Width:**

0.755 inches

**Body Length:**

0.755 inches

**Body Width:**

0.755 inches

**Body Height:**

2.250 inches

**Case Material:**

Metal

**Actuator Length:**

0.755 inches

**Actuator Style:**

Rectangular

**Actuator Width:**

0.755 inches

**Actuator Color:**

Red single actuator

**Illuminated Actuator Color:**

Red single actuator

**Actuator Inscription:**

Test fire tube single actuator

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Panel

**Features Provided:**

Actuator seal

**Nonpile-up Contact Arrangement:**

4 pole, double throw, one position momentary single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 2.500 amperes inductive dc and 1.500 amperes lamp dc and 5.000 amperes resistive ac and 2.500 amperes inductive ac and 1.500 amperes lamp ac

**Special Features:**

Full display lens

**Precious Material And Location:**

Contact surfaces gold and contacts silver

**Unable To Decode:**

Unable to decode and unable to decode

**Terminal Type And Quantity:**

19 pin

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0