## NSN 5930-01-135-2047

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-135-2047
Body Style:
Panel mount
Hazardous Locations/environmental Protection:
Moisture proof and shock proof
Overall Length:
0.755 inches
Overall Height:
3.060 inches
Overall Width:
0.755 inches
Body Length:
0.755 inches
Body Width:
0.755 inches
Body Height:
2.250 inches
Case Material:
Metal
Actuator Length:
0.755 inches
Actuator Style:
Rectangular
Actuator Width:
0.755 inches
Actuator Color:
Red single actuator
Illuminated Actuator Color:
Red single actuator
Actuator Inscription:
Test fire tube single actuator
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Panel  Factorian Bravidado
Features Provided:
Actuator seal  Nonnilo-un Contact Arrangement:
Nonpile-up Contact Arrangement:  4 pole double throw one position momentary single switch unit
4 pole, double throw, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:
5 000 amperes resistive do and 2 500 amperes industive do an

5.000 amperes resistive dc and 2.500 amperes inductive dc and 1.500 amperes lamp dc and 5.000 amperes resistive ac and 2.500 amperes inductive ac and 1.500 amperes lamp ac

## NSN 5930-01-135-2047

Push Switch - Page 2 of 2



Special Features:
Full display lens
Precious Material And Location:
Contact surfaces gold and contacts silver
Unable To Decode:
Unable to decode and unable to decode
Terminal Type And Quantity:
19 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

**Fiig:** A053a0