

View Online at <https://aerobasegroup.com/nsn/5930-01-135-2635>

Thread Length:

0.375 inches single mounting facility

Overall Length:

4.030 inches

First Flat Length:

0.250 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

1.625 inches single actuator

Overall Diameter:

0.968 inches

Nonturn Device Radius:

0.375 inches at 5: 00 o'clock

Individual Section Quantity:

1

Nonturn Device Type:

Pin at 5: 00 o'clock

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

2 single section rear

Throw Quantity:

4 single section rear

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 lowest dc voltage rating at sea level

Switch Actuator Indexing Position Quantity:

4 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes single section rear

Switch Actuator Positioning Increment:

36.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

500.0 milliamperes resistive load highest dc voltage rating at sea level

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unf single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0