

View Online at <https://aerobasegroup.com/nsn/5930-01-135-4027>

**Thread Class:**

3a single pressure connection

**Overall Length:**

3.340 inches

**Pressure Switch Type:**

Differential

**Width Across Flats:**

1.000 inches

**Mounting Method:**

Inlet connection

**Features Provided:**

Electrical box connector

**Thready Qty Per Inch (tpi):**

16 single pressure connection

**Contact Action Stimulus:**

Increase

**Thread Size:**

0.750 inches single pressure connection

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary

**Terminal Type:**

Connector, receptacle

**Contact Load Current Rating:**

22.0 amperes resistive load second voltage

**Contact Adjustability:**

Deactuation point not adjustable and actuation point not adjustable

**Contact Stimulus Rating:**

16.00 actuation point pounds per square inch and 15.00 deactuation point pounds per square inch and 1.00 differential point pounds per square inch

**Contact Voltage Rating In Volts:**

28.0 dc at sea level second voltage

**Pressure Connector Type:**

Flared, threaded external single connection

**Media For Which Designed:**

Gas or liquid

**Thread Series Designator:**

Unf single pressure connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A048b0