## NSN 5930-01-135-5133

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-135-5133

**Overall Length:** 0.956 inches **Overall Height:** 0.300 inches **Body Diameter:** 0.660 centimeters **End Application:** 6665-01-081-8140 **Tempurature Sensing Element Type:** Internal sensor **Operating Tempurature Rating:** Between -10.0 degrees fahrenheit and 250.0 degrees fahrenheit **Mounting Method:** Clamp **Features Provided:** Hermetically sealed case **Contact Action Stimulus:** Increase **Nonpile-up Contact Arrangement:** 1 pole, single throw, normally open, momentary action **Terminal Type:** Tab, solder lug **Contact Load Current Rating:** 2.0 amperes resistive load second voltage and 1.0 amperes inductive load second voltage and 1.0 amperes lamp load second voltage **Contact Adjustability:** Deactuation point not adjustable and actuation point not adjustable **Contact Stimulus Rating:** 0.00 actuation point degrees fahrenheit and 2.00 deactuation point degrees fahrenheit and 5.00 deactuation point degrees fahrenheit and 2.00 differential point degrees fahrenheit and 5.00 differential point degrees fahrenheit **Contact Voltage Rating In Volts:** 28.0 dc at sea level second voltage Frequency In Hertz: 60.0 first voltage Media For Which Designed: Gas or liquid **Style Designator:** Disc **Test Data Document:** 

81349-mil-s-24236 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Specification Data:**

81349-mil-s-24236/20 government specification

## Shelf Life:

N/a

## NSN 5930-01-135-5133

Thermostatic Switch - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A048b0